

# Manual Total Station

## Zoom35 Pro Series



### Superior accXess10 EDM

- > 1,000 m non-prism range
- > 10,000 m prism range
- Pin size laser beam



### Colour touch screen

- Large 3.5" Q-VGA display
- Fast navigation
- Brilliant readability



### Easy connectivity

- USB memory stick
- Bluetooth® transfer
- Plug and Play technology

# Zoom35 Pro Series

With non-prism measurements of 1,000 m, the all new Zoom35 Pro opens a new class of total stations for all those requiring highest performance on all levels.



**Zoom35 Pro accXess10** Long-range distance measurement on reflector and > 1,000m reflectorless\*

## Angle measurements

Accuracy	1" (0.3 mgon), 2" (0.6 mgon), 3" (0.9 mgon), 5" (1.5 mgon)
Display resolution	0.1" (0.1 mgon)
Method	Absolute, continuous, diametrical
Compensation	Quadruple axis

## Distance measurements

Prism	3,500 m / 2 mm + 2 ppm
Long range	10,000 m / 5 mm + 2 ppm
Typ. meas. time	1 s**
Reflectorless	> 1,000 m / 2 mm + 2 ppm***
Footprint	8 x 20 mm****

## Physical specifications

Weight	5.1 kg (incl. battery & tribrach)
Operating temp.	-30°C to 50°C*****
Protection class	IP55 dust- and waterproof
Humidity	95 %, non-condensing

**Distance meter (Reflector Mode):** Laser class 1 in accordance with IEC 60825-1 resp. EN 60825-1; **Laser plummet:** Laser class 2 in accordance with IEC 60825-1 resp. EN 60825-1, **Distance meter (Reflectorless Mode accXess™):** Laser class 3R in accordance with IEC 60825-1 resp. EN 60825-1



Copyright GeoMax AG.  
Illustrations, descriptions and technical specifications are not binding and may change.  
0615 / 808081 en

With the proven accXess10 technology, the Zoom35 Pro features an intelligent distance measurement engine designed for outstanding speed and highest accuracy even on extreme long ranges. A longer measurement range means a wider operational coverage and significant less time lost with switching set ups. All this in combination with the extra-wide colour touch screen, Bluetooth®, USB memory stick and a complete suite of application provide the total station with the longest non-prism range in the market – making sure it “works when you do”.

## Interface

Keyboard	Full alphanumeric
Display	3.5" Quarter-VGA colour touch screen (320x240 pixel), 10 lines x 30 characters, self heating, illuminated
Data recording	Internal memory 50,000 pts
Interface	USB, serial & external power
Removable memory	USB memory stick
Bluetooth®	Device Class 1

## Power supply

Internal battery	Removable Li-Ion 4,4 Ah / 7,4 V
Operating time	36 h (continuous angle), 9 hours (continuous distance measurement every 30s)

## Plummet

Type	Laser point, adjustable brightness
Accuracy	1.5 mm at 1.5 m instrument height

## Operating system

Windows®	Embedded CE
----------	-------------

\* Optimal conditions to Kodak Grey Card (90% reflectivity)

\*\* IR-Quick mode

\*\*\* > 500 m: 4 mm + 2 ppm

\*\*\*\* At 50 m distance

\*\*\*\*\* Optional tested polar version, standard -20°C to 50°C

All trademarks and trade names are those of their respective owners.



**GeoMax AG**  
www.geomax-positioning.com  
info@geomax-positioning.com

Works when you do